


seamless bend 90° type 3

[short name: NB\\*](#)

DIN 2605



## technical product sheet

D	s	r	Tol	kg	Art.-Nr.
13,5	2,3			0,020	NB-013-023
17,2	1,6	23,0	+/- 2,5	0,027	NB-017-016
17,2	2,3	23,0	+/- 2,5	0,032	NB-017-023
20,0	1,5	25,0	+/- 2,5	0,028	NB-020-015
20,0	2,0	25,0	+/- 2,5	0,039	NB-020-020
21,3	2,0	26,0	+/- 2,5	0,040	NB-021-020
21,3	2,6	26,0	+/- 2,5	0,062	NB-021-026
26,9	2,0	29,0	+/- 2,5	0,060	NB-026-020
26,9	2,6	29,0	+/- 2,5	0,067	NB-026-026
26,9	2,9	29,0	+/- 2,5	0,000	NB-026-029
28,0	1,5	32,0	+/- 2,5	0,000	NB-028-015
33,7	2,0	38,0	+/- 2,5	0,000	NB-033-020
33,7	3,2	38,0	+/- 2,5	0,152	NB-033-032
38,0	2,0	45,0	+/- 2,5	0,120	NB-038-020
42,4	2,0	48,0	+/- 2,5	0,000	NB-042-020
42,4	2,6	48,0	+/- 2,5	0,190	NB-042-026
42,4	3,2	48,0	+/- 2,5	0,225	NB-042-032
42,4	3,6	48,0	+/- 2,5	0,194	NB-042-036
48,3	2,0	57,0	+/- 3,0	0,230	NB-048-020
48,3	2,6	57,0	+/- 3,0	0,000	NB-048-026
48,3	3,2	57,0	+/- 3,0	0,320	NB-048-032
48,3	3,6	57,0	+/- 3,0	0,289	NB-048-036
48,3	4,0	57,0	+/- 3,0	0,450	NB-048-040
57,0	2,9	72,0	+/- 3,0	0,450	NB-057-029
60,3	2,0	76,0	+/- 3,0	0,000	NB-060-020
60,3	2,7	76,0	+/- 3,0	0,520	NB-060-027
60,3	2,9	76,0	+/- 3,0	0,530	NB-060-029
60,3	3,6	76,0	+/- 3,0	2,725	NB-060-036
60,3	4,0	76,0	+/- 3,0	0,680	NB-060-040
76,1	2,9	95,0	+/- 3,0	1,281	NB-076-029
76,1	3,6	95,0	+/- 3,0	1,011	NB-076-036
76,1	4,0	95,0	+/- 3,0	1,032	NB-076-040
88,9	2,6	115,0	+/- 3,0	1,040	NB-088-026
88,9	3,0	115,0	+/- 3,0	0,000	NB-088-030
88,9	3,2	115,0	+/- 3,0	1,150	NB-088-032
88,9	4,0	115,0	+/- 3,0	1,556	NB-088-040

D	s	r	Tol	kg	Art.-Nr.
88,9	5,5	115,0	+/- 3,0	2,201	NB-088-055
108,0	4,0	143,0	+/- 3,0	2,540	NB-108-040
108,0	5,0	143,0	+/- 3,0	0,000	NB-108-050
114,3	2,6	153,0	+/- 3,0	1,960	NB-114-026
114,3	3,0	153,0	+/- 3,0	2,300	NB-114-030
114,3	3,6	153,0	+/- 3,0	2,529	NB-114-036
114,3	4,5	153,0	+/- 3,0	3,140	NB-114-045
114,3	6,3	153,0	+/- 3,0	0,000	NB-114-063
133,0	4,0	181,0	+/- 3,0	3,626	NB-133-040
139,7	4,0	191,0	+/- 4,0	6,899	NB-139-040
139,7	5,0	191,0	+/- 4,0	5,310	NB-139-050
139,7	6,3			0,000	NB-139-063
168,3	3,2	228,0	+/- 4,0	0,000	NB-168-032
168,3	4,5	228,0	+/- 4,0	0,000	NB-168-045
168,3	5,0	228,0	+/- 4,0	20,450	NB-168-050
168,3	6,3	228,0	+/- 4,0	0,000	NB-168-063
219,1	6,3	305,0	+/- 4,0	0,000	NB-219-063
219,1	8,1	305,0	+/- 4,0	0,000	NB-219-081

available material: 1.4841

Butt welding fittings > bends > seamless > type 3, r=1,5xD > 90° > other dimensions