


kříž s 2 redukovanými hrdly
přivařené
délka dle DIN 2615

[zkratka označení: KRKR*](#)



technický list výrobku

D	D2	s	L	l	h	Art.-Nr.
42,4	26,9	2,0	96	48,0	48,0	KRKR-042-026X20-4L
60,3	26,9	2,0	128	64,0	44,0	KRKR-060-026X20-JL
60,3	33,7	2,0	128	64,0	51,0	KRKR-060-033X20-2L
76,1	60,0	3,0	152	76,0	70,0	KRKR-076-060X30-2L
76,1	60,3	2,0	152	76,0	70,0	KRKR-076-060X20-1L
88,9	76,1	2,0	172	86,0	83,0	KRKR-088-076X20-2L
104,0	54,0	2,0	210	105,0	89,0	KRKR-104-054X20-NL
104,0	88,9	2,0	210	105,0	98,0	KRKR-104-088X20-NL
139,7	114,3	2,0	248	124,0	117,0	KRKR-139-114X20-1L
154,0	104,0	2,0	286	143,0	125,0	KRKR-154-104X20-JL
154,0	104,0	2,0	286	143,0	125,0	KRKR-154-104X20-NL
168,3	76,1	3,0	286	143,0	120,0	KRKR-168-076X30-4L
168,3	88,9	2,0	286	143,0	124,0	KRKR-168-088X20-JL
168,3	114,3	3,0	286	143,0	130,0	KRKR-168-114X30-4L
168,3	139,7	2,0	286	143,0	137,0	KRKR-168-139X20-1L
219,1	88,9	2,0	356	178,0	150,0	KRKR-219-088X20-2L
219,1	114,3	3,0	356	178,0	156,0	KRKR-219-114X30-4L
219,1	114,3	3,0	356	178,0	156,0	KRKR-219-114X30-JL
273,0	168,3	3,0	432	216,0	194,0	KRKR-273-168X30-4L
323,9	168,3	3,0	508	254,0	229,0	KRKR-323-168X30-2L

dostupné jakosti: na poptávku

Přivařovací fitinky > T-X-Y-kusy > svařované > s výstupy > redukováná hrdla