



bend 15° with plain ends
pipe connection on both sides
DVGW-approval for water

[short name: PFPB15*](#)



technical product sheet

| Rohr-AD | DW | kg | Art.-Nr. |
|---------|------|-------|------------------|
| 28,0 | EPDM | 0,157 | PRFI-PB-028-4-15 |
| 35,0 | EPDM | 0,383 | PRFI-PB-035-4-15 |
| 54,0 | EPDM | 0,924 | PRFI-PB-054-4-15 |

available material: ask

Systems > press fittings > bends > plain ends > 15°



Press fittings

Properties

M-contour / V-contour (suitable pressing tools can be found at www.heco.de/pressfittings/technik)

DIN-DVGW approval for drinking water optional for gas up to 1000 mbar (label: yellow)

Nominal pressure, water applications, max. 16 bar

Nominal pressure, gases, max. 5 bar (PN5 / GT5)

Material: Stainless steel 1.4401 / 1.4571 (copper available as an option)

Sealing rings

| Material | Color | Application | Temperature | Pressure |
|-------------|--------|-------------|----------------|-------------|
| EPDM | black | water | -20° - +120° C | max. 16 bar |
| FKM/ Viton* | green | solar | -30° - +180° C | max. 16 bar |
| FPM/ Viton* | gray | vapor | -20° - +150° C | max. 5 bar |
| NBR* | red | oils | -20° - +120° C | max. 16 bar |
| HNBR* | yellow | gas | -20° - + 70° C | max. 5 bar |

(*) = optional