



trubka svařovaná, tepelně zprac.

[zkratka označení: RO-G*](#)

EN 10217-7/ PK1

Tol. EN 1127 D3/T3



technický list výrobku

D	s	kg	Art.-Nr.
6,0	1,0	0,125	RO-006-G10
8,0	1,0	0,175	RO-008-G10
8,0	1,5	0,244	RO-008-G15
10,0	1,0	0,225	RO-010-G10
10,0	1,5	0,319	RO-010-G15
12,0	1,0	0,275	RO-012-G10
12,0	1,5	0,394	RO-012-G15
13,0	1,5	0,432	RO-013-G15
14,0	1,0	0,326	RO-014-G10
14,0	1,5	0,470	RO-014-G15
14,0	2,0	0,601	RO-014-G20
15,0	1,0	0,351	RO-015-G10
15,0	1,5	0,507	RO-015-G15
15,0	2,0	0,651	RO-015-G20
16,0	1,0	0,377	RO-016-G10
16,0	1,5	0,545	RO-016-G15
16,0	2,0	0,701	RO-016-G20
18,0	1,0	0,426	RO-018-G10
18,0	1,5	0,620	RO-018-G15
18,0	2,0	0,801	RO-018-G20
20,0	1,0	0,476	RO-020-G10
20,0	1,5	0,695	RO-020-G15
20,0	2,0	0,901	RO-020-G20
22,0	1,0	0,527	RO-022-G10
22,0	1,5	0,770	RO-022-G15
22,0	2,0	1,002	RO-022-G20
25,0	1,0	0,601	RO-025-G10
25,0	1,5	0,883	RO-025-G15
25,0	2,0	1,152	RO-025-G20
25,0	2,5	1,409	RO-025-G25
28,0	1,5	0,995	RO-028-G15
28,0	2,0	1,302	RO-028-G20
30,0	1,0	0,726	RO-030-G10
30,0	1,5	1,070	RO-030-G15
30,0	2,0	1,402	RO-030-G20
30,0	2,5	1,722	RO-030-G25

D	s	kg	Art.-Nr.
30,0	3,0	2,028	RO-030-G30
32,0	1,5	1,146	RO-032-G15
32,0	2,0	1,502	RO-032-G20
35,0	1,5	1,258	RO-035-G15
35,0	2,0	1,653	RO-035-G20
35,0	2,5	2,035	RO-035-G25
38,0	1,5	1,371	RO-038-G15
38,0	2,0	1,803	RO-038-G20
38,0	3,0	2,629	RO-038-G30
40,0	1,0	0,977	RO-040-G10
40,0	1,5	1,446	RO-040-G15
40,0	2,0	1,903	RO-040-G20
40,0	3,0	2,779	RO-040-G30
43,0	1,5	1,559	RO-043-G15
44,5	1,5	1,615	RO-044-G15
44,5	2,0	2,128	RO-044-G20
44,5	2,6	2,728	RO-044-G26
45,0	2,0	2,160	RO-045-G20
50,0	1,5	1,822	RO-050-G15
50,0	2,0	2,404	RO-050-G20
51,0	2,0	2,454	RO-051-G20
51,0	2,6	3,151	RO-051-G26
52,0	1,0	1,277	RO-052-G10
52,0	1,5	1,897	RO-052-G15
54,0	2,0	2,604	RO-054-G20
57,0	2,0	2,754	RO-057-G20
57,0	3,0	4,137	RO-057-G30
63,5	1,6	2,480	RO-063-G16
69,0	2,0	3,366	RO-069-G20
70,0	2,0	3,405	RO-070-G20
70,0	2,9	4,873	RO-070-G29
84,0	2,0	4,107	RO-084-G20
101,6	2,0	4,988	RO-101-G20
104,0	2,0	4,852	RO-104-G20
108,0	2,0	5,308	RO-108-G20
108,0	3,0	7,888	RO-108-G30
108,0	4,0	10,417	RO-108-G40

dostupné jakosti: 1.4301

Montážní materiál > Trubky > kulaté > svařované > trubky k rozvodu médií > další > žíhaná