


bend 90° SR

ASME B 16.9

[short name: ANSI-BS*](#)


technical product sheet

Zoll	Sched.	D	s	r	Typ	kg	Art.-Nr.
1"	10S	33,4	2,77	25,4	geschw.	0,000	ANSI-BS-100-010-J
1"	10S	33,4	2,77	25,4	nahtlos	0,000	ANSI-BS-100-010-J
1"	10S	33,4	2,77	25,4	nahtlos	0,080	ANSI-BS-100-010-N
1"	40S	33,4	3,38	25,4	nahtlos	0,105	ANSI-BS-100-040-N
1 1/4"	10S	42,2	2,77	31,8	nahtlos	0,140	ANSI-BS-114-010-J
1 1/4"	10S	42,2	2,77	31,8	nahtlos	0,000	ANSI-BS-114-010-N
1 1/4"	40S	42,2	3,56	31,8	nahtlos	0,000	ANSI-BS-114-040-J
1 1/4"	40S	42,2	3,56	31,8	nahtlos	0,200	ANSI-BS-114-040-N
1 1/2"	10S	48,3	2,77	38,1	nahtlos	0,000	ANSI-BS-112-010-J
1 1/2"	10S	48,3	2,77	38,1	nahtlos	0,000	ANSI-BS-112-010-N
1 1/2"	40S	48,3	3,68	38,1	geschw.	0,360	ANSI-BS-112-040-N
1 1/2"	40S	48,3	3,68	38,1	nahtlos	0,000	ANSI-BS-112-040-J
1 1/2"	40S	48,3	3,68	38,1	nahtlos	0,242	ANSI-BS-112-040-N
2"	10S	60,3	2,77	50,8	geschw.	0,000	ANSI-BS-200-010-J
2"	10S	60,3	2,77	50,8	nahtlos	0,000	ANSI-BS-200-010-J
2"	10S	60,3	2,77	50,8	nahtlos	0,000	ANSI-BS-200-010-N
2"	40S	60,0	3,91	50,8	geschw.	0,647	ANSI-BS-200-040-N
2"	40S	60,3	3,91	50,8	nahtlos	0,450	ANSI-BS-200-040-J
2"	40S	60,3	3,91	50,8	nahtlos	0,453	ANSI-BS-200-040-N
2 1/2"	10S	73,0	3,05	63,5	nahtlos	0,000	ANSI-BS-212-010-J
2 1/2"	10S	73,0	3,05	63,5	nahtlos	0,587	ANSI-BS-212-010-N
3"	10S	88,9	3,05	76,2	nahtlos	0,840	ANSI-BS-300-010-J
3"	10S	88,9	3,05	76,2	nahtlos	0,791	ANSI-BS-300-010-N
3"	40S	88,9	5,49	76,2	nahtlos	1,378	ANSI-BS-300-040-J
3"	40S	88,9	5,49	76,2	nahtlos	0,000	ANSI-BS-300-040-N
4"	10S	114,3	3,05	101,6	nahtlos	1,538	ANSI-BS-400-010-J
4"	10S	114,3	3,05	101,6	nahtlos	0,000	ANSI-BS-400-010-N
4"	40S	114,3	6,02	101,6	nahtlos	0,000	ANSI-BS-400-040-J
4"	40S	114,3	6,02	101,6	nahtlos	2,783	ANSI-BS-400-040-N
5"	10S	141,3	3,40	127,0	nahtlos	2,547	ANSI-BS-500-010-N
6"	10S	168,3	3,40	152,4	geschw.	0,000	ANSI-BS-600-010-J
6"	10S	168,3	3,40	152,4	nahtlos	0,000	ANSI-BS-600-010-N
6"	40S	168,3	7,11	152,4	geschw.	0,000	ANSI-BS-600-040-J
6"	40S	168,3	7,11	152,4	geschw.	0,000	ANSI-BS-600-040-N
8"	10S	219,1	3,76	203,2	geschw.	0,000	ANSI-BS-800-010-N
8"	40S	219,1	8,18	203,2	geschw.	0,000	ANSI-BS-800-040-J

Zoll	Sched.	D	s	r	Typ	kg	Art.-Nr.
8"	40S	219,1	8,18	203,2	geschw.	0,000	ANSI-BS-800-040-N
8"	40S	219,1	8,18	203,2	nahtlos	0,000	ANSI-BS-800-040-J
8"	40S	219,1	8,18	203,2	nahtlos	0,000	ANSI-BS-800-040-N
10"	10S	273,1	4,19	254,0	geschw.	12,400	ANSI-BS-A00-010-J
10"	10S	273,1	4,19	254,0	nahtlos	16,700	ANSI-BS-A00-010-J
10"	10S	273,1	4,19	254,0	nahtlos	16,700	ANSI-BS-A00-010-N
10"	20	273,1	6,35	254,0	nahtlos	0,000	ANSI-BS-A00-020-J
10"	40S	273,1	9,27	254,0	nahtlos	30,020	ANSI-BS-A00-040-J
10"	40S	273,1	9,27	254,0	nahtlos	0,000	ANSI-BS-A00-040-N
12"	10S	323,9	4,57	304,8	geschw.	0,000	ANSI-BS-B00-010-J
12"	40S	323,9	9,53	304,8	nahtlos	0,000	ANSI-BS-B00-040-N
14"	40S	355,6	9,53	355,6	geschw.	0,000	ANSI-BS-C00-040-J
14"	40S	355,6	9,53	355,6	geschw.	52,000	ANSI-BS-C00-040-N

available material: ask

Butt welding fittings > ANSI / ASME > bends > 90° Short Radius