


welding socket

[short name: SM\\*](#)


## technical product sheet

| G      | D    | s   | t    | D3 | l | L  | kg    | Art.-Nr.   |
|--------|------|-----|------|----|---|----|-------|------------|
| 1/4"   | 13,5 | 2,0 | 12,0 | 18 | 5 | 21 | 0,019 | SM-014-000 |
| 3/8"   | 17,2 | 2,0 | 13,0 | 21 | 5 | 23 | 0,020 | SM-038-000 |
| 1/2"   | 21,3 | 2,0 | 16,0 | 25 | 6 | 27 | 0,036 | SM-012-000 |
| 3/4"   | 26,9 | 2,0 | 17,5 | 32 | 6 | 28 | 0,057 | SM-034-000 |
| 1"     | 33,7 | 2,6 | 20,0 | 39 | 6 | 31 | 0,090 | SM-100-000 |
| 1 1/4" | 42,4 | 2,6 | 22,5 | 48 | 6 | 34 | 0,130 | SM-114-000 |
| 1 1/2" | 48,3 | 2,6 | 22,5 | 55 | 8 | 36 | 0,170 | SM-112-000 |
| 2"     | 60,3 | 2,6 | 26,5 | 65 | 8 | 40 | 0,190 | SM-200-000 |

available material: 1.4404

Threaded fittings &gt; fittings &gt; PN 10 (ECO-Line) &gt; sockets &gt; special versions &gt; welding sockets