




Svařovaná trubka broušená

[zkratka označení: GR- -G*](#)

tepelně zpracovaná

EN 10217-7/ PK1

Tol. EN 1127 D3/T3



technický list výrobku

D	s	kg	Art.-Nr.
10,0	1,0	0,225	GR-010-G10
10,0	1,5	0,319	GR-010-G15
12,0	1,0	0,275	GR-012-G10
12,0	1,5	0,394	GR-012-G15
14,0	2,0	0,601	GR-014-G20
15,0	1,5	0,507	GR-015-G15
15,0	2,0	0,700	GR-015-G20
16,0	1,5	0,545	GR-016-G15
18,0	1,5	0,620	GR-018-G15
20,0	1,0	0,476	GR-020-G10
20,0	1,5	0,695	GR-020-G15
20,0	2,0	0,901	GR-020-G20
22,0	2,0	1,002	GR-022-G20
25,0	1,0	0,601	GR-025-G10
25,0	1,5	0,883	GR-025-G15
25,0	2,0	1,152	GR-025-G20
25,0	2,5	1,409	GR-025-G25
25,0	3,0	1,653	GR-025-G30
28,0	1,5	0,995	GR-028-G15
28,0	2,0	0,995	GR-028-G20
30,0	2,0	1,402	GR-030-G20
30,0	2,5	1,722	GR-030-G25
30,0	3,0	2,028	GR-030-G30
32,0	1,5	1,145	GR-032-G15
32,0	2,0	1,502	GR-032-G20
35,0	2,0	1,653	GR-035-G20
38,0	2,0	1,800	GR-038-G20
40,0	1,5	1,450	GR-040-G15
40,0	2,0	1,903	GR-040-G20
44,5	2,0	2,128	GR-044-G20
48,3	3,6	4,029	GR-048-G36
50,0	2,0	2,410	GR-050-G20

dostupné jakosti: na poptávku

Montážní materiál > Trubky > kulaté > svařované > další > žíhaná, broušená

