

seamless precision tube

[short name: NR.P*](#)

DIN 2642/ EN ISO 1127

D4/T3 DIN 2391 / EN 10305/1



technical product sheet

| D | s | kg | Art.-Nr. |
|------|-----|-------|------------|
| 6,0 | 1,0 | 0,125 | NR-006-P10 |
| 6,0 | 1,5 | 0,169 | NR-006-P15 |
| 6,0 | 2,0 | 0,200 | NR-006-P20 |
| 8,0 | 1,0 | 0,175 | NR-008-P10 |
| 8,0 | 1,5 | 0,244 | NR-008-P15 |
| 10,0 | 1,0 | 0,225 | NR-010-P10 |
| 10,0 | 1,5 | 0,319 | NR-010-P15 |
| 10,0 | 2,0 | 0,402 | NR-010-P20 |
| 12,0 | 1,0 | 0,275 | NR-012-P10 |
| 12,0 | 1,5 | 0,394 | NR-012-P15 |
| 12,0 | 2,0 | 0,501 | NR-012-P20 |
| 12,0 | 2,5 | 0,595 | NR-012-P25 |
| 14,0 | 2,0 | 0,601 | NR-014-P20 |
| 14,0 | 3,0 | 0,826 | NR-014-P30 |
| 15,0 | 1,0 | 0,351 | NR-015-P10 |
| 15,0 | 1,5 | 0,507 | NR-015-P15 |
| 15,0 | 2,0 | 0,651 | NR-015-P20 |
| 16,0 | 1,5 | 0,350 | NR-016-P15 |
| 16,0 | 2,0 | 0,701 | NR-016-P20 |
| 16,0 | 2,5 | 0,845 | NR-016-P25 |
| 16,0 | 3,0 | 0,977 | NR-016-P30 |
| 17,2 | 1,6 | 0,625 | NR-017-P16 |
| 17,2 | 2,0 | 0,761 | NR-017-P20 |
| 17,2 | 2,9 | 1,038 | NR-017-P29 |
| 18,0 | 1,0 | 0,426 | NR-018-P10 |
| 18,0 | 1,5 | 0,620 | NR-018-P15 |
| 18,0 | 2,0 | 0,801 | NR-018-P20 |
| 18,0 | 2,5 | 0,970 | NR-018-P25 |
| 20,0 | 1,0 | 0,620 | NR-020-P10 |
| 20,0 | 1,5 | 0,695 | NR-020-P15 |
| 20,0 | 2,0 | 0,901 | NR-020-P20 |
| 22,0 | 1,5 | 1,080 | NR-022-P15 |
| 22,0 | 2,0 | 1,080 | NR-022-P20 |
| 25,0 | 2,5 | 1,409 | NR-025-P25 |
| 28,0 | 1,5 | 0,995 | NR-028-P15 |
| 28,0 | 2,0 | 1,302 | NR-028-P20 |

| D | s | kg | Art.-Nr. |
|------|-----|-------|------------|
| 35,0 | 2,0 | 1,653 | NR-035-P20 |
| 38,0 | 4,0 | 3,405 | NR-038-P40 |
| 38,0 | 5,0 | 4,132 | NR-038-P50 |
| 42,0 | 2,0 | 2,003 | NR-042-P20 |
| 42,0 | 3,0 | 2,930 | NR-042-P30 |

available material: ask

Installation supplies > tubes > round > seamless > for hydraulic tubing