


bend 90°, grinded
type 5 welded DIN 26054

[short name: BG5*](#)



technical product sheet

| K | D | s | r | kg |
|----------|------|-----|-----|-------|
| Korn 240 | 25,0 | 2,0 | 55 | 0,000 |
| Korn 240 | 26,9 | 2,0 | 58 | 0,108 |
| Korn 240 | 33,7 | 2,0 | 73 | 0,180 |
| Korn 240 | 38,0 | 2,0 | 85 | 0,000 |
| Korn 240 | 40,0 | 2,0 | 95 | 0,130 |
| Korn 240 | 42,4 | 2,0 | 93 | 0,291 |
| Korn 240 | 42,4 | 2,6 | 93 | 0,363 |
| Korn 240 | 48,3 | 2,0 | 108 | 0,387 |
| Korn 240 | 48,3 | 2,6 | 108 | 0,000 |
| Korn 240 | 54,0 | 2,0 | 122 | 0,000 |
| Korn 240 | 60,3 | 2,0 | 135 | 0,542 |
| Korn 240 | 70,0 | 2,0 | 160 | 0,000 |
| Korn 240 | 76,1 | 2,9 | 175 | 0,000 |

available material: ask

Butt welding fittings > bends > welded > decoration-bends > grinded > type 5 ($r=2,5xD$) > 90°