


kříž s 2 redukovanými hrdly
přivařené
délka dle DIN 2615

[zkratka označení: KRKR*](#)



technický list výrobku

| D | D2 | s | L | l | h | Art.-Nr. |
|-------|-------|-----|-----|-------|-------|--------------------|
| 42,4 | 26,9 | 2,0 | 96 | 48,0 | 48,0 | KRKR-042-026X20-4L |
| 60,3 | 26,9 | 2,0 | 128 | 64,0 | 44,0 | KRKR-060-026X20-JL |
| 60,3 | 33,7 | 2,0 | 128 | 64,0 | 51,0 | KRKR-060-033X20-2L |
| 76,1 | 60,0 | 3,0 | 152 | 76,0 | 70,0 | KRKR-076-060X30-2L |
| 76,1 | 60,3 | 2,0 | 152 | 76,0 | 70,0 | KRKR-076-060X20-1L |
| 88,9 | 76,1 | 2,0 | 172 | 86,0 | 83,0 | KRKR-088-076X20-2L |
| 104,0 | 54,0 | 2,0 | 210 | 105,0 | 89,0 | KRKR-104-054X20-NL |
| 104,0 | 88,9 | 2,0 | 210 | 105,0 | 98,0 | KRKR-104-088X20-NL |
| 139,7 | 114,3 | 2,0 | 248 | 124,0 | 117,0 | KRKR-139-114X20-1L |
| 154,0 | 104,0 | 2,0 | 286 | 143,0 | 125,0 | KRKR-154-104X20-JL |
| 154,0 | 104,0 | 2,0 | 286 | 143,0 | 125,0 | KRKR-154-104X20-NL |
| 168,3 | 76,1 | 3,0 | 286 | 143,0 | 120,0 | KRKR-168-076X30-4L |
| 168,3 | 88,9 | 2,0 | 286 | 143,0 | 124,0 | KRKR-168-088X20-JL |
| 168,3 | 114,3 | 3,0 | 286 | 143,0 | 130,0 | KRKR-168-114X30-4L |
| 168,3 | 139,7 | 2,0 | 286 | 143,0 | 137,0 | KRKR-168-139X20-1L |
| 219,1 | 88,9 | 2,0 | 356 | 178,0 | 150,0 | KRKR-219-088X20-2L |
| 219,1 | 114,3 | 3,0 | 356 | 178,0 | 156,0 | KRKR-219-114X30-4L |
| 219,1 | 114,3 | 3,0 | 356 | 178,0 | 156,0 | KRKR-219-114X30-JL |
| 273,0 | 168,3 | 3,0 | 432 | 216,0 | 194,0 | KRKR-273-168X30-4L |
| 323,9 | 168,3 | 3,0 | 508 | 254,0 | 229,0 | KRKR-323-168X30-2L |

dostupné jakosti: na poptávku

Přivařovací fitinky > T-X-Y-kusy > svařované > s výstupy > redukováná hrdla