

bend 15° with plain ends
pipe connection on both sides
DVGW-approval for water

[short name: PFPB15*](#)




technical product sheet

Rohr-AD	DW	kg	Art.-Nr.
28,0	EPDM	0,157	PRFI-PB-028-4-15
35,0	EPDM	0,383	PRFI-PB-035-4-15
54,0	EPDM	0,924	PRFI-PB-054-4-15

available material: ask

Systems > press fittings > bends > plain ends > 15°



Press fittings

Properties

M-contour / V-contour (suitable pressing tools can be found at www.heco.de/pressfittings/technik)

DIN-DVGW approval for drinking water optional for gas up to 1000 mbar (label: yellow)

Nominal pressure, water applications, max. 16 bar

Nominal pressure, gases, max. 5 bar (PN5 / GT5)

Material: Stainless steel 1.4401 / 1.4571 (copper available as an option)

Sealing rings

Material	Color	Application	Temperature	Pressure
EPDM	black	water	-20° - +120° C	max. 16 bar
FKM/ Viton*	green	solar	-30° - +180° C	max. 16 bar
FPM/ Viton*	gray	vapor	-20° - +150° C	max. 5 bar
NBR*	red	oils	-20° - +120° C	max. 16 bar
HNBR*	yellow	gas	-20° - + 70° C	max. 5 bar

(*) = optional