


bend 90° SR

[short name: ANSI-BS*](#)

ASME B 16.9



technical product sheet

Typ	Zoll	Sched.	D	s	r	kg	Art.-Nr.
geschw.	1"	10S	33,4	2,77	25,4	0,000	ANSI-BS-100-010-J
geschw.	1 1/2"	40S	48,3	3,68	38,1	0,360	ANSI-BS-112-040-N
geschw.	2"	10S	60,3	2,77	50,8	0,000	ANSI-BS-200-010-J
geschw.	2"	40S	60,0	3,91	50,8	0,647	ANSI-BS-200-040-N
geschw.	6"	10S	168,3	3,40	152,4	0,000	ANSI-BS-600-010-J
geschw.	6"	40S	168,3	7,11	152,4	0,000	ANSI-BS-600-040-J
geschw.	6"	40S	168,3	7,11	152,4	0,000	ANSI-BS-600-040-N
geschw.	8"	10S	219,1	3,76	203,2	0,000	ANSI-BS-800-010-N
geschw.	8"	40S	219,1	8,18	203,2	0,000	ANSI-BS-800-040-J
geschw.	8"	40S	219,1	8,18	203,2	0,000	ANSI-BS-800-040-N
geschw.	10"	10S	273,1	4,19	254,0	12,400	ANSI-BS-A00-010-J
geschw.	12"	10S	323,9	4,57	304,8	0,000	ANSI-BS-B00-010-J
geschw.	14"	40S	355,6	9,53	355,6	0,000	ANSI-BS-C00-040-J
geschw.	14"	40S	355,6	9,53	355,6	52,000	ANSI-BS-C00-040-N
nahtlos	1"	10S	33,4	2,77	25,4	0,000	ANSI-BS-100-010-J
nahtlos	1"	10S	33,4	2,77	25,4	0,080	ANSI-BS-100-010-N
nahtlos	1"	40S	33,4	3,38	25,4	0,105	ANSI-BS-100-040-N
nahtlos	1 1/4"	10S	42,2	2,77	31,8	0,140	ANSI-BS-114-010-J
nahtlos	1 1/4"	10S	42,2	2,77	31,8	0,000	ANSI-BS-114-010-N
nahtlos	1 1/4"	40S	42,2	3,56	31,8	0,000	ANSI-BS-114-040-J
nahtlos	1 1/4"	40S	42,2	3,56	31,8	0,200	ANSI-BS-114-040-N
nahtlos	1 1/2"	10S	48,3	2,77	38,1	0,000	ANSI-BS-112-010-J
nahtlos	1 1/2"	10S	48,3	2,77	38,1	0,000	ANSI-BS-112-010-N
nahtlos	1 1/2"	40S	48,3	3,68	38,1	0,000	ANSI-BS-112-040-J
nahtlos	1 1/2"	40S	48,3	3,68	38,1	0,242	ANSI-BS-112-040-N
nahtlos	2"	10S	60,3	2,77	50,8	0,000	ANSI-BS-200-010-J
nahtlos	2"	10S	60,3	2,77	50,8	0,000	ANSI-BS-200-010-N
nahtlos	2"	40S	60,3	3,91	50,8	0,450	ANSI-BS-200-040-J
nahtlos	2"	40S	60,3	3,91	50,8	0,453	ANSI-BS-200-040-N
nahtlos	2 1/2"	10S	73,0	3,05	63,5	0,000	ANSI-BS-212-010-J
nahtlos	2 1/2"	10S	73,0	3,05	63,5	0,587	ANSI-BS-212-010-N
nahtlos	2 1/2"	40S	73,0	5,16	63,5	1,300	ANSI-BS-212-040-N
nahtlos	3"	10S	88,9	3,05	76,2	0,840	ANSI-BS-300-010-J
nahtlos	3"	10S	88,9	3,05	76,2	0,791	ANSI-BS-300-010-N
nahtlos	3"	40S	88,9	5,49	76,2	1,378	ANSI-BS-300-040-J
nahtlos	3"	40S	88,9	5,49	76,2	0,000	ANSI-BS-300-040-N

Typ	Zoll	Sched.	D	s	r	kg	Art.-Nr.
nahtlos	4"	10S	114,3	3,05	101,6	1,538	ANSI-BS-400-010-J
nahtlos	4"	10S	114,3	3,05	101,6	0,000	ANSI-BS-400-010-N
nahtlos	4"	40S	114,3	6,02	101,6	0,000	ANSI-BS-400-040-J
nahtlos	4"	40S	114,3	6,02	101,6	2,783	ANSI-BS-400-040-N
nahtlos	5"	10S	141,3	3,40	127,0	2,547	ANSI-BS-500-010-N
nahtlos	6"	10S	168,3	3,40	152,4	0,000	ANSI-BS-600-010-N
nahtlos	8"	40S	219,1	8,18	203,2	0,000	ANSI-BS-800-040-J
nahtlos	8"	40S	219,1	8,18	203,2	0,000	ANSI-BS-800-040-N
nahtlos	10"	10S	273,1	4,19	254,0	16,700	ANSI-BS-A00-010-J
nahtlos	10"	10S	273,1	4,19	254,0	16,700	ANSI-BS-A00-010-N
nahtlos	10"	20	273,1	6,35	254,0	0,000	ANSI-BS-A00-020-J
nahtlos	10"	40S	273,1	9,27	254,0	30,020	ANSI-BS-A00-040-J
nahtlos	10"	40S	273,1	9,27	254,0	0,000	ANSI-BS-A00-040-N
nahtlos	12"	40S	323,9	9,53	304,8	0,000	ANSI-BS-B00-040-N

available material: ask

Butt welding fittings > ANSI / ASME > bends > 90° Short Radius