


bend 90° SR

[short name: ANSI-BS\\*](#)

ASME B 16.9



### technical product sheet

Typ	Zoll	Sched.	D	s	r	kg
geschw.	1 1/2"	40S	48,3	3,68	38,1	0,360
geschw.	2"	10S	60,3	2,77	50,8	0,000
geschw.	2"	40S	60,0	3,91	50,8	0,647
geschw.	6"	10S	168,3	3,40	152,4	0,000
geschw.	6"	40S	168,3	7,11	152,4	0,000
geschw.	8"	10S	219,1	3,76	203,2	6,300
geschw.	8"	40S	219,1	8,18	203,2	0,000
geschw.	10"	10S	273,1	4,19	254,0	12,400
nahtlos	1"	10S	33,4	2,77	25,4	0,080
nahtlos	1"	40S	33,4	3,38	25,4	0,105
nahtlos	1 1/4"	10S	42,2	2,77	31,8	0,140
nahtlos	1 1/4"	40S	42,2	3,56	31,8	0,200
nahtlos	1 1/2"	10S	48,3	2,77	38,1	0,000
nahtlos	1 1/2"	40S	48,3	3,68	38,1	0,242
nahtlos	2"	10S	60,3	2,77	50,8	0,000
nahtlos	2"	40S	60,3	3,91	50,8	0,453
nahtlos	2 1/2"	10S	73,0	3,05	63,5	0,587
nahtlos	2 1/2"	40S	73,0	5,16	63,5	1,300
nahtlos	3"	10S	88,9	3,05	76,2	0,840
nahtlos	3"	40S	88,9	5,49	76,2	1,430
nahtlos	4"	10S	114,3	3,05	101,6	1,538
nahtlos	4"	40S	114,3	6,02	101,6	2,783
nahtlos	4"	80S	114,3	8,56	101,6	0,000
nahtlos	5"	10S	141,3	3,40	127,0	2,547
nahtlos	6"	10S	168,3	3,40	152,4	0,000
nahtlos	8"	40S	219,1	8,18	203,2	0,000
nahtlos	10"	10S	273,1	4,19	254,0	16,700
nahtlos	10"	20	273,1	6,35	254,0	0,000
nahtlos	10"	40S	273,1	9,27	254,0	30,020

available material: ask

Butt welding fittings > ANSI / ASME > bends > 90° Short Radius

