


45° bend LR
ASME B 16.9

[short name: ANSI-45*](#)



technical product sheet

Typ	Zoll	Sched.	D	s	l
geschw.	1/2"	10S	21,3	2,11	15,9
geschw.	2"	10S	60,3	2,77	34,9
geschw.	4"	10S	114,3	3,05	63,5
geschw.	5"	10S	141,3	3,40	79,4
geschw.	6"	10S	168,3	3,40	95,3
geschw.	6"	40S	168,3	7,11	95,3
geschw.	8"	10S	219,1	3,76	127,0
geschw.	8"	40S	219,1	8,18	127,0
geschw.	10"	10S	273,1	4,19	159,0
geschw.	10"	40S	273,1	9,27	159,0
geschw.	12"	10S	323,9	4,57	190,5
geschw.	12"	40S	323,9	9,53	190,5
geschw.	18"	10S	457,2	4,78	285,8
nahtlos	1/2"	160	21,3	4,78	15,9
nahtlos	1"	10S	33,4	2,77	22,2
nahtlos	1"	80S	33,4	4,55	22,2
nahtlos	1"	160	33,4	6,35	22,2
nahtlos	1 1/2"	10S	48,3	2,77	28,6
nahtlos	1 1/2"	40S	48,3	3,68	28,6
nahtlos	2"	10S	60,3	2,77	34,9
nahtlos	2"	40S	60,3	3,91	34,9
nahtlos	2"	80S	60,3	5,54	34,9
nahtlos	2 1/2"	10S	73,0	3,05	44,5
nahtlos	2 1/2"	40S	73,0	5,16	44,5
nahtlos	3"	10S	88,9	3,05	50,8
nahtlos	3"	40S	88,9	5,49	50,8
nahtlos	4"	10S	114,3	3,05	63,5
nahtlos	4"	40S	114,3	6,02	63,5
nahtlos	6"	10S	168,3	3,40	95,3
nahtlos	6"	40S	168,3	7,11	95,3
nahtlos	8"	10S	219,1	3,76	127,0

available material: ask

Butt welding fittings > ANSI / ASME > bends > 45° Long Radius

