


hose piece

[short name: GEKA.T*](#)

Geka - quick coupling



technical product sheet

Zoll	di	SM	L	L2	Abnahme	kg	Art.-Nr.
3/8"	10	Standard	40	28	-	0,072	GEKA-038-0TÜ-M
1/2"	13	Standard	40	28	-	0,095	GEKA-012-0TÜ-M
5/8"	16	Standard	44	32	-	0,000	GEKA-058-0TÜ-M
3/4"	19	Standard	44	32	-	0,120	GEKA-034-0TÜ-M
3/4"	19	Standard	44	32	DVGW	0,092	GEKA-034-0TÜ-M-DVGW
1"	25	Standard	50	37	-	0,128	GEKA-100-0TÜ-M
1 1/4"	32	Standard	60	48	-	0,179	GEKA-114-0TÜ-M
1 1/2"	38	Standard	63	48	-	0,204	GEKA-112-0TÜ-M

available material: Messing

Systems > quick couplings > Geka > hose pieces



Claw distance

The claw distance for all GEKA couplings is 40mm.

This means all products in the GEKA program are compatible and can be connected to all connectors without requiring reducers.

Pressure and Temperature Resistance

The choice of form sealing ring determines the pressure range as well as the temperature range.

Application	NBR	Viton
Pressure range	up to 40 bar	up to 30 bar
Temperature range	-30°C to +100°C	-20°C to +200°C

