



bend 90° SR

[short name: BS.*](#)

ASME B 16.9



technical product sheet

Typ	Zoll	Sched.	D	s	r	kg
geschw.	1 1/2"	40S	48,3	3,68	38,1	0,360
geschw.	2"	10S	60,3	2,77	50,8	0,000
geschw.	2"	40S	60,3	3,91	50,8	0,647
geschw.	3"	10S	88,9	3,05	76,2	0,840
geschw.	3"	40S	88,9	5,49	76,2	0,000
geschw.	6"	10S	168,3	3,40	152,4	4,960
geschw.	6"	40S	168,3	7,11	152,4	0,000
geschw.	8"	10S	219,1	3,76	203,2	6,300
geschw.	8"	40S	219,1	8,18	203,2	21,500
geschw.	10"	10S	273,1	4,19	254,0	12,400
geschw.	12"	10S	323,9	4,57	304,8	16,700
nahtlos	1"	10S	33,4	2,77	25,4	0,090
nahtlos	1"	40S	33,4	3,38	25,4	0,105
nahtlos	1 1/4"	10S	42,2	2,77	31,8	0,162
nahtlos	1 1/4"	40S	42,2	3,56	31,8	0,200
nahtlos	1 1/2"	10S	48,3	2,77	38,1	0,174
nahtlos	1 1/2"	40S	48,3	3,68	38,1	0,242
nahtlos	1 1/2"	80S	48,3	5,08	38,1	0,000
nahtlos	2"	10S	60,3	2,77	50,8	0,390
nahtlos	2"	40S	60,3	3,91	50,8	0,453
nahtlos	2 1/2"	10S	73,0	3,05	63,5	0,587
nahtlos	2 1/2"	40S	73,0	5,16	63,5	1,300
nahtlos	3"	10S	88,9	3,05	76,2	0,840
nahtlos	3"	40S	88,9	5,49	76,2	1,430
nahtlos	4"	10S	114,3	3,05	101,6	1,720
nahtlos	4"	40S	114,3	6,02	101,6	3,120
nahtlos	4"	80S	114,3	8,56	101,6	0,000
nahtlos	5"	10S	141,3	3,40	127,0	2,547
nahtlos	6"	10S	168,3	3,40	152,4	0,000
nahtlos	6"	40S	168,3	7,11	152,4	7,070
nahtlos	8"	40S	219,1	8,18	203,2	0,000
nahtlos	10"	10S	273,1	4,19	254,0	16,700
nahtlos	10"	20	273,1	6,35	254,0	19,500
nahtlos	10"	40S	273,1	9,27	254,0	30,020

available material: 304L, 316L

created 24.05.2023 20:15

Typ

Zoll

Sched.

D

s

r

kg

Butt welding fittings > ANSI / ASME > bends > 90° Short Radius