


šestihránná vsuvka
cylindr. závit
podle ISO 228

[zkratka označení: R.207Z*](#)



technický list výrobku

G	l1	L	SW	d	kg	Art.-Nr.
1/4"	6,5	20,5	17	7,5	0,020	DN-014-6KZ
3/8"	6,5	20,5	22	10,0	0,030	DN-038-6KZ
1/2"	11,0	32,0	27	14,0	0,050	DN-012-6KZ
3/4"	11,0	32,0	32	19,0	0,070	DN-034-6KZ
1"	12,0	35,0	41	24,5	0,120	DN-100-6KZ
1 1/4"	14,0	41,0	50	32,0	0,210	DN-114-6KZ
1 1/2"	14,0	41,0	55	38,0	0,230	DN-112-6KZ
2"	16,0	46,0	65	50,0	0,310	DN-200-6KZ

dostupné jakosti: 1.4404

Fitinky závitové > fitinky > PN 50/100 > vsuvky > R-207 Z



Hexagon nipple

R-207

- > manufactured from solid material – „threaded version“
- > material 1.4404/ AISI 316L
- > BSP-thread according to ISO 7/1 (once DIN 2999); optional with NPT-thread

Design pressure

Size	Mpa
to 1"	10,0
off 1 1/4"	6,4
off 2"	4,0