



4-hran. zátka, kuželový závit

[zkratka označení: R.238\\*](#)


## technický list výrobku

| R      | L  | l1 | SW | PN  | kg    | Art.-Nr.   |
|--------|----|----|----|-----|-------|------------|
| 1/8"   | 16 | 6  | 7  | 100 | 0,010 | ST-018-4KT |
| 1/4"   | 18 | 9  | 9  | 100 | 0,020 | ST-014-4KT |
| 3/8"   | 20 | 9  | 10 | 100 | 0,030 | ST-038-4KT |
| 1/2"   | 22 | 12 | 11 | 100 | 0,040 | ST-012-4KT |
| 3/4"   | 27 | 13 | 16 | 100 | 0,090 | ST-034-4KT |
| 1"     | 32 | 15 | 19 | 100 | 0,160 | ST-100-4KT |
| 1 1/4" | 36 | 17 | 22 | 64  | 0,290 | ST-114-4KT |
| 1 1/2" | 37 | 17 | 22 | 64  | 0,390 | ST-112-4KT |
| 2"     | 43 | 22 | 27 | 64  | 0,690 | ST-200-4KT |
| 2 1/2" | 46 | 24 | 32 | 40  | 1,170 | ST-212-4KT |
| 3"     | 50 | 27 | 36 | 40  | 1,740 | ST-300-4KT |

dostupné jakosti: 1.4404

[Fitinky závitové](#) > [fitinky](#) > [PN 50/100](#) > [víčka/zátky](#) > [R-238](#)



### square plug

R-238

- > made from a solid material - "turned design"
- > Material 1.4404/ AISI 316L
- > BSP-thread acc. to ISO 7/1 (once DIN 2999); optional with NPT-thread
- > with PED-pressure approval

Design pressure

| Size        | Mpa  |
|-------------|------|
| up to 1"    | 10,0 |
| from 1 1/4" | 6,4  |
| from 2"     | 4,0  |