


spojovací tvarovka TC
oboustranně svěrná hrdla
dle DIN 32676

[zkratka označení: TCVS*](#)



technický list výrobku

Reihe	d3	DN	D	s	L
Reihe A	34	20	23,0	1,5	60
Reihe A	34	20	23,0	1,5	100
Reihe A	50,5	25	29,0	1,5	50
Reihe A	50,5	25	29,0	1,5	70
Reihe A	50,5	25	29,0	1,5	75
Reihe A	50,5	25	29,0	1,5	100
Reihe A	50,5	25	29,0	1,5	150
Reihe A	50,5	25	29,0	1,5	200
Reihe A	50,5	25	29,0	1,5	500
Reihe A	50,5	40	41,0	1,5	50
Reihe A	50,5	40	41,0	1,5	70
Reihe A	50,5	40	41,0	1,5	100
Reihe A	50,5	40	41,0	1,5	200
Reihe A	50,5	40	41,0	1,5	300
Reihe A	64	50	53,0	1,5	50
Reihe A	64	50	53,0	1,5	60
Reihe A	64	50	53,0	1,5	70
Reihe A	64	50	53,0	1,5	75
Reihe A	64	50	53,0	1,5	80
Reihe A	64	50	53,0	1,5	100
Reihe A	64	50	53,0	1,5	120
Reihe A	64	50	53,0	1,5	200
Reihe A	64	50	53,0	1,5	500
Reihe A	64	50	53,0	1,5	150

dostupné jakosti: na poptávku

Systémy > spojky clamp > spojovací tvarovky



TC connection

Stainless steel construction welded using protective gas, welded, pickled in the dipping bath, and passivated.

Consisting of a longitudinally welded tube acc. to DIN EN 10357 or EN 10217-7 and 2 clamping sockets DIN 32676.

Dimension range

Series A (DIN): DN 10 to DN 200

Series B (ISO): 13,5 to 219,1

Mounting length acc. to your default.