


šroubovací zátka DIN 910
BANDED, šestihránná hlava

[zkratka označení: VS910*](#)



technický list výrobku

G	L	l1	D	SW	kg	Art.-Nr.
1/8"	17	8	14	10	0,010	VS-018-000
1/4"	21	12	18	13	0,020	VS-014-000
3/8"	21	12	22	17	0,040	VS-038-000
1/2"	26	14	26	19	0,070	VS-012-000
3/4"	30	16	32	24	0,130	VS-034-000
1"	32	16	39	27	0,200	VS-100-000
1 1/4"	33	16	49	30	0,340	VS-114-000
1 1/2"	33	16	55	30	0,390	VS-112-000
2"	40	20	68	36	0,700	VS-200-000

dostupné jakosti: V4A

Fitinky závitové > fitinky > PN 10 (ECO-Line) > víčka/zátky > DIN 910



Trubkový závit Whitworth dle DIN/ISO 228-G

Utěsnění spojů je provedeno vzájemným zatlačením dvou ploch těsnění mimo závit a vložení vhodného těsnění

G	Počet chodů	h	P	i
1/8"	28	0,581	0,907	8
1/4"	19	0,856	1,337	12
3/8"	19	0,856	1,337	12
1/2"	14	1,162	1,814	14
3/4"	14	1,162	1,814	16
1"	11	1,479	2,309	18
1 1/4"	11	1,479	2,309	20
1 1/2"	11	1,479	2,309	22
2"	11	1,479	2,309	24

G	Boky-Ø	max. Ø A pro AG	min. Ø jádra für IG
1/8"	9,147	9,728	8,566
1/4"	12,301	13,157	11,445
3/8"	15,806	16,662	14,950
1/2"	19,793	20,955	18,631
3/4"	25,279	26,441	24,117
1"	31,770	33,249	30,291
1 1/4"	40,431	41,910	38,952
1 1/2"	46,324	47,803	44,845
2"	58,135	59,614	56,656

